

# AOT Specifications



## Key Features

- Sunlight Readable
- LED Backlight
- -20°C~60°C Wide Temp.
- Low Power Consumption
- High Shock & Vibration Resistance
- 90% High Uniformity
- Low EMI Noise
- Wide Dimming
- Multiple Mounting Choices
- 70000hrs Life Expectancy



## OLF/OLH1075 (SHAR LQ104S1LG61)

Model No.	OLF1075	OLH1075
<b>LCD Display</b>	10.4" LED Backlight LCD	10.4" LED Backlight LCD
<b>Display Area</b>	211.2 x 158.4 mm	210.4 x 157.8 mm
<b>Brightness</b>	1000 cd/m <sup>2</sup>	1000 cd/m <sup>2</sup>
<b>Resolution</b>	800 x 600 (SVGA)	800 x 600 (SVGA)
<b>Contrast Ratio</b>	500 : 1	500 : 1
<b>Pixel Pitch (mm)</b>	0.264(H) x 0.264(V)	0.264(H) x 0.264(V)
<b>Viewing Angle</b>	150°(H), 150°(V)	150°(H), 150°(V)
<b>Display Colors</b>	262K colors	262K colors
<b>Response Time</b>	35ms	35ms
<b>Sync</b>	LVDS x 1 Channel	LVDS x 1 Channel
<b>Power Consumption</b>	16.2W	21.2W
<b>LED Driving Board</b>	LI D10A	LI D10A
<b>Control Board (Optional)</b>		AD5621GA (Standard)
<b>F / R Control Button</b>		Power Switch, Menu, Select (+,-), Auto
<b>OSD Menu</b>		Brightness, Contrast, H/V Position, Color, Phase, Clock...
<b>Dimensions (WxHxD)</b>	246.5.1x175x13.75mm	246.5.1x175x13.75mm
<b>Weight</b>	825g	925g
<b>Optional</b>	<input checked="" type="checkbox"/> Touch Screen	

Specifications are subject to change without notice. All brands or product names are trademarks or registered trademarks of their respective companies.



<b>Control Board (Optional)</b>	AD5621GA/AD5621GD/AD5766GDVA
<input checked="" type="checkbox"/> AD5621GA	VGA+Audio
<input checked="" type="checkbox"/> AD5621GD	VGA+DVI
<input checked="" type="checkbox"/> AD5766GDVA	VGA+CVBS+S-Video+Audio (Optional DVI / Component)
<b>F / R Control Button</b>	5 Key / 4 Key (Optional)
<input checked="" type="checkbox"/> 5 Key	Power Switch, Menu, Select (+,-), Auto
<input checked="" type="checkbox"/> 4 Key	Power Switch, Menu, Select (+,-)

OLF= Panel+Driving Board+AOT

OLH= Panel+Driving Board+Control Board+AOT