

Platform Specifications



Platform

Key Features

- Sunlight Readable
- High Contrast Ratio
- LVDS
- Long Lamp Life
- Thin and Light
- 6 CCFL



SLD1041(AUO G104SN05)

Model No.	SLD1041
LCD Display	10.4" TFT LCD Module
Display Area	211.2 x 158.4 mm
Brightness	1500 cd/m ²
Resolution	800x600 (SVGA)
Contrast Ratio	500 : 1
Pixel Pitch (mm)	0.264(H) x 0.264(V)
Viewing Angle	+60°~-60°(H), +40°~-60°(V)
Display Colors	262K colors
Response Time	35ms (Typical)
Sync	LVDS
Power Consumption	30W
Inverter	LI 0610A
Control Board (Optional)	AD5621GA (Standard)
F / R Control Button	Power Switch, Menu, Select (+,-), Auto
OSD Menu	Brightness, Contrast, H/V Position, Color, Phase, Clock....
Dimensions (WxHxD)	340x228x54.2mm
Weight	2.8kgs
Optional	<input checked="" type="checkbox"/> AOT <input checked="" type="checkbox"/> Touch Screen

Specifications are subject to change without notice. All brands or product names are trademarks or registered trademarks of their respective companies.

Control Board (Optional)	AD5621GA/AD5621GD/AD5766GDVA
<input checked="" type="checkbox"/> AD5621GA	VGA+Audio
<input checked="" type="checkbox"/> AD5621GD	VGA+DVI
<input checked="" type="checkbox"/> AD5766GDVA	VGA+CVBS+S-Video+Audio (Optional DVI / Component)
F / R Control Button	5 Key / 4 Key (Optional)
<input checked="" type="checkbox"/> 5 Key	Power Switch, Menu, Select (+,-), Auto
<input checked="" type="checkbox"/> 4 Key	Power Switch, Menu, Select (+,-)

SLO= Open Frame
SLD= Industrial Casing



