

Platform Specifications



Platform

Key Features

- Sunlight Readable
- LED Backlight
- -20°C~60°C Wide Temp.
- Low Power Consumption
- High Shock & Vibration Resistance
- 90% High Uniformity
- Low EMI Noise
- Wide Dimming
- Multiple Mounting Choices
- 70000hrs Life Expectancy



SLD1555 (CMO G150X1-L02)

Model No.	SLD1555
LCD Display	15" LED Backlight LCD
Display Area	304.128 x 228.096mm
Brightness	1500 cd/m ²
Resolution	1024 x 768 (XGA)
Contrast Ratio	700 : 1
Pixel Pitch (mm)	0.297(H) x 0.297(V)
Viewing Angle	160°(H), 160°(V)
Display Colors	16,194,277 colors
Response Time	25ms (Typical)
Sync	LVDS x 1 Channel
Power Consumption	30W
LED Driving Board	LI D15A
Control Board (Optional)	AD5621GA (Standard)
F / R Control Button	Power Switch, Menu, Select (+,-), Auto
OSD Menu	Brightness, Contrast, H/V Position, Color, Phase, Clock....
Dimensions (WxHxD)	389x325x61.6mm
Weight	4.62kgs
Optional	<input checked="" type="checkbox"/> Touch Screen

Specifications are subject to change without notice. All brands or product names are trademarks or registered trademarks of their respective companies.

Control Board (Optional)	AD5621GA/AD5621GD/AD5766GDVA/AD1501GDV
<input checked="" type="checkbox"/> AD5621GA	VGA+Audio
<input checked="" type="checkbox"/> AD5621GD	VGA+DVI
<input checked="" type="checkbox"/> AD5766GDVA	VGA+CVBS+S-Video+Audio (Optional DVI / Component)
<input checked="" type="checkbox"/> AD1501GDV	VGA+DVI+S-Video
F / R Control Button	5 Key / 4 Key (Optional)
<input checked="" type="checkbox"/> 5 Key	Power Switch, Menu, Select (+,-), Auto
<input checked="" type="checkbox"/> 4 Key	Power Switch, Menu, Select (+,-)

SLO= Open Frame

SLD= Industrial Casing



