

Covered with elegant stainless steel housing, build-in double ventilation fan system, SLD2312 can deliver the best quality image even in severe outdoor environment. Input signals include VGA, optional AV, S-Video and TV Tuner for all cable channel reception.



SLD2312 TFT LCD Monitor

LCD Display	23" TFT Active LCD Panel
Screen Dimension	22.95 inch
Display Area	508.152(H)x285.696(V)mm
Display Mode	Normally Black
Recommended Resolution	1366x768
Pixel Pitch	0.372(H)x0.372(V)
Luminance	500 cd/m ² (Typ.)
Contrast Ratio	500:1(Typ.)
Response Time	25 ms (Typ.)
Viewing Angle	+85°~-85° (H), +85°~-85° (V)
Display Color	16.7 M (RGB 8-bit data)
PC Connector In	D-sub 15 pin (VGA input)
Signal Connector In (Option)	AV/S-video/Component/Rremote Control
Horizontal/Vertical Frequency	Hf:80KHz; Vf: 56~75Hz
Audio	5W x 2
Cooling Fan	2
AC/DC Power Adapter Input	AC 100~240V, 50~60 Hz
AC/DC Power Adapter Output	DC 12V / 6.66A
Power Consumption	80W (Max.)
Weight	N/W:14.0 kgs ; G/W:16.0kgs
Dimension (no box packing)	546.6 (W) x 394.2 (H) x 79.6 (D)mm
Accessories	User's Manual, VGA Cable

*Specifications are subject to change without notice.
 All brands or product names are trademarks or registered trademarks of their respective companies.*

8F-2, No.133, Lane 235,
 Bau-chiau Rd.,
 Shin-dian City, Taipei, Taiwan
 Tel:+886-2-8919-1858
 FAX:+886-2-8919-1300
 www.litemax.com