



SSF/SSH1624-B

16.3" LCD, 350nits, LED backlight, 1366x238 ultra-wide aspect ratio 16:2.8

The SSF/SSH1624-B is a 16.3 inch color TFT-LCD display with special aspect ratio 16:2.8 and wide resolution 1366 x 238. It is Litemax's Spanpixel series product which designed for high brightness with power efficiency LED backlight. It provides LCD panel with specific aspect ratios and sunlight readable for digital signage, public transportation, exhibition hall, department store, and vending machine.

Key Features

- Resizing LCD
- Ultra Wide Screen 16:2.8
- LED Backlight
- Brightness 350nits
- Low Power Consumption
- BL MTBF: 100,000 hours



Specifications

| Model Name | SSF/SSH1624-B |
|--------------------------|--|
| Description | 16.3" TFT LCD, 350nits LED backlight, 1366x238 |
| Screen Size | 16.3" |
| Display Area (mm) | 409.800(H) x 71.400(V) |
| Brightness | 350 cd/m ² |
| Resolution | 1366x238 |
| Aspect Ratio | 16 : 2.8 |
| Contrast Ratio | 1000 : 1 |
| Pixel Pitch (mm) | 0.300(H) x 0.300(V) |
| Pixel Per Inch (PPI) | 84 |
| Viewing Angle | 178°(H),178°(V) |
| Color Saturation (NTSC) | 77% |
| Display Colors | 16.7M |
| Response Time (Typical) | 16ms |
| Panel Interface | LVDS |
| AD Board Input Interface | VGA, DVI-D, HDMI |
| Input Power | DC12V |
| Power Consumption | 7.2W, 8.8W (with AD board) |
| OSD Key | 4 Keys (Power Switch, Menu, +, -) |
| OSD Control | Brightness, Color, Contrast, Auto Turing, H/V Position...etc |
| Dimensions (mm) | 431.8(H) x 95.8(V) x 15.1(T) |
| Bezel Size(U/B/L/R) | 12.1/12.4/11/11 mm |
| Weight (Net) | 0.5kg |
| Operating Temperature | 0 °C ~ 50 °C |
| Storage Temperature | -20 °C ~ 60 °C |

SSF= Panel + LED Driving Board

SSH= Panel + LED Driving Board + AD Control Board



Specifications are subject to change without notice.
All brands or product names are trademarks or registered trademarks of their respective companies.





Mechanical Drawing

Outline Dimensions

Unit:mm





Connector View
SCALE 10 : 1

Note :

1. THE DIMENSION EXCLUDES DEFORMATION.
2. LED B/L CONNECTOR : H112K-P06N-00B OR COMPATIBLE.
3. I/F CONNECTOR TO BE JAE FI-X30H OR EQUIVALENT.
4. M3 USER HOLE SCREW TORQUE 3.0 kgf- cm MAX , HOLE Depth 7.5mm Max.



Ordering Information

| Part Number | Description |
|-----------------|--|
| SSF1624-BNN-A01 | 16.3",350nits,1366*238,LID16C,10in1,V1 |
| SSH1624-BNN-Q01 | 16.3",350nits,1366*238,AD8891GDH w/LID,DC12V,5in1,V1 |

Optional Accessories

| Part Number | Description |
|--------------|--|
| 840612051212 | ADAPTER,AC/DC,12V/5 A,60W,Power-Din-4P,CWT,G99-ABF060F-N022,Efficiency-level-6,R |
| 810618301010 | CABLE,POWER,AC,1830mm USA type |
| 810618301090 | CABLE,POWER,AC,1830mm Europe type |
| 810618301050 | CABLE,POWER,AC,1830mm UK type |
| 810618301170 | CABLE,POWER,AC,1830mm Australia type |
| 810618301031 | CABLE,POWER,AC,1830mm Japan type |
| | |

Customer request

| | |
|-------|---------------------------------------|
| Touch | SCT (Single-Touch), PCT (Multi-Touch) |
| Glass | Tempered glass, AR coating..... |
| | |