



DLF/DLH2150-T

21.5" TFT LCD, 2000 nits LED Backlight, 1920x1080

The DLF/DLH2150-T is a 21.5 inch industrial grade sunlight readable LCD, with high brightness 2000 nits, it produces sharp images, crisp text and lifelike colors. The Durapixel LED backlight technology ensures high reliability and low power consumption, suitable for outdoor application, kiosk, factory automation, military, transportation and gaming application.

Key Features

- High Brightness 2000 nits
- Sunlight Readable
- LED Backlight
- Low Power Consumption
- Wide Temperature (-20°C ~ 70°C)
- LCD Blackening Defect Free (Hi-Tni 110°C)
- BL MTBF: 100,000 hours



Specifications

Model Name	DLF/DLH2150-T
Description	21.5" TFT LCD, 1600 nits LED Backlight, 1920x1080
Screen Size	21.5"
Display Area (mm)	476.06(H) x 267.79(V)
Brightness	2000 cd/m ²
Resolution	1920x1080
Aspect Ratio	16:9
Contrast Ratio	960:1
Pixel Pitch (mm)	0.24795(H) x 0.24795(V)
Pixel Per Inch (PPI)	102
Viewing Angle	178°(H),178°(V)
Color Saturation (NTSC)	74%
Display Colors	16.7M
Response Time (Typical)	20ms
Panel Interface	LVDS
Input Interface	HDMI, DP
Input Power	DC12V
Power Consumption	22W (25W with AD Board)
OSD Key	4 Keys (Power Switch, Menu, +, -)
OSD Control	Brightness, Color, Contrast, Auto Tuning, H/V Position...etc
Dimensions (mm)	497.6(W) x 292.4(H) x 13.35(D) mm
Bezel Size(U/B/L/R)	12.207/12.207/10.768/10.768 mm
Weight (Net)	1.85kg
Operating Temperature	-20°C ~ 70°C
Storage Temperature	-30°C ~ 80°C

DLF= Panel + LED Driving Board


DLH= Panel + LED Driving Board + AD Control Board




Specifications are subject to change without notice.
All brands or product names are trademarks or registered trademarks of their respective companies.



Outline Dimensions

Unit: mm





Note

1. Resolution : 1920 x 1080
2. Unspecified Tolerance : ± 0.50 mm
3. "()" marks the reference dimension
4. Front case is black paint.
5. M3 User Hole Max Torque 4.5 kg-cm



Ordering Information

Part Number	Description
DLF2150-TNN-A11	21.5",2000nits,1920x1080,T2070,HTni,LID21C,5in1,V1
DLH2150-TNN-T11	21.5",2000nits,1920x1080,T2070,HTni,LID21C,AD68862HP,DC12V,5in1,V1

Optional Accessories

Part Number	Description
840612051212	ADAPTER,AC/DC,12V/5A,60W,Power-Din-4P,CWT,G99-ABF060F-N022,Efficiency-level-6,R
810618301010	CABLE,POWER,AC,1830mm USA type
810618301090	CABLE,POWER,AC,1830mm Europe type
810618301050	CABLE,POWER,AC,1830mm UK type
810618301170	CABLE,POWER,AC,1830mm Australia type
810618301031	CABLE,POWER,AC,1830mm Japan type

Customer request

Touch	PCAP (Multi-Touch)
Glass	Tempered glass, AR coating.....